

# AUTOMATE YOUR SURVEY PROCESS

## IMAGE SCANNING – A FASTER, SIMPLER ROUTE TO DATA CAPTURE

### Cost-effective survey scanning

Enhanced with innovative features, the Fujitsu fi-6130 offers outstanding price/performance value in a compact footprint, conserving both space and budget.

### Ultimate in performance

With duplex scanning performance of up to 80 images per minute in monochrome and greyscale, the fi-6130 also delivers uncompromised high-resolution performance of up to 60 images per minute in colour at an astounding 300 dpi.

### Advanced survey scanning technology

Engineered with one of the most advanced paper separation features in their class, the fi-6130 is one of the first workgroup scanners equipped with reversing roller technology, resulting in exceptional feeding reliability for an even wider variety of document weights.

### Robust functionality

The fi-6130 features an automatic document feeder (ADF) capable of scanning documents up to 10 feet long and can feed up to three hard cards continuously or an embossed card up to 1.4 mm in thickness.

Additionally, the fi-6130 combines the security of Ultrasonic Double Feed Detection with the efficiency of Intelligent MultiFeed Function (iMFF) so that intentional double-feeds, such as a taped receipt or sticky note, can be manually bypassed while double-feed detection is enabled.

### Complete Adobe® software

Fujitsu fi-6130 scanner conveniently includes everything in the box to get you scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for our Advance Exchange Program, provides peace-of mind.

### Enhanced for the ultimate in performance and reliability

- Fast, 40ppm / 80ipm scanning in monochrome and greyscale
- Exceptional 300 dpi colour scanning at 30ppm / 60ipm
- Advanced paper handling technology for the ultimate in feeding reliability
- Scan to PDF, file, print or batch
- Robust 50-page Automatic Document Feeder (ADF) with enhanced hard embossed card scanning
- Comes with Kofax® VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro
- One-year warranty

### Find out more

At Speedwell we can provide you with scanning technology that gives you all these benefits at a reasonable cost.

Call us for a quote on  
**01223 851703**



## TECHNICAL SPECIFICATIONS

Image Sensor Type	fi-6130	Colour Charge Coupled Device (CCD) x 2
	fi-6230	Colour Charge Coupled Device (CCD) x 3
Light Source	White cold cathode discharge lamp	
Optical Resolution 600 dpi	600 dpi	
Output Resolution <sup>1</sup>	Colour (24 bit)	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi) <sup>2</sup>
	Greyscale (8 bit)	
	Monochrome	
Output Format	Colour: 24 bit, 8 bit/4 bit; Greyscale: 8 bit, 4 bit; Monochrome: 1 bit	
AD Converter	1024 levels (10 bit)	
Output Mode	Dither / Error diffusion	

### Scanning speeds

Output (Letter/A4 size) <sup>3</sup>		Simplex	Duplex
Colour <sup>4</sup>	200 dpi	30 ppm	60 ipm
	300 dpi	30 ppm	60 ipm
Greyscale / Monochrome	200 dpi	40 ppm	80 ipm
	300 dpi	30 ppm	60 ipm
ADF Capacity <sup>5</sup>	50 Sheets (letter/A4, 20 lb.)		
Document size	ADF minimum	2 in. x 3 in. (52mm x 74mm)	
	ADF maximum	8.5 in. x 14 in. (Legal)	
	Long Document	8.4 in. x 122 in. (10 feet) <sup>8</sup>	
	Flatbed (fi-6230 only)	8.5 in x 11.69 in. (216mm x 297mm)	
ADF Feeding Paper Weight (Thickness)	Normal	11 to 56.2 lb. (41 to 210g/m <sup>2</sup> )	
	A8 sheets	34 to 56.2 lb. (127 to 210g/m <sup>2</sup> )	
	Card <sup>6</sup> (1.4 mm) <sup>7</sup>	Portrait and Landscape feeding <sup>8</sup>	
Interface	USB 2.0 / USB 1.1 (B type connector)		

### Physical Specifications

Power requirements	100 – 240 VAC, 50/60 Hz	
Power consumption	fi-6130	38W or less (Sleep: less than 6.2W)
	fi-6230	45W or less (Sleep: less than 6.2W)
Dimensions (WxDxH) <sup>10</sup>	fi-6130	11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)
	fi-6230	11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)
Weight	fi-6130	9.24 lb. (4.2 kg)
	fi-6230	19.36 lb. (8.8 kg)
Environmental Compatibility <sup>11</sup>	ENERGY STAR <sup>®</sup> and RoHS	
Operating Environment	Temperature	42° to 95°F (5° to 35°C)
	Relative humidity	20% – 80% (non-condensing)
Inbox Contents	TWAIN, ISIS™, USB cable, AC adapter	
Bundled Software	Adobe <sup>®</sup> Acrobat <sup>®</sup> Standard, Kofax <sup>®</sup> VRS <sup>®</sup> Professional and ScandAll Pro	
Options	Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6230)	
OS Support	Microsoft <sup>®</sup> Windows <sup>®</sup> 2000 Professional / Microsoft <sup>®</sup> XP (32 bit/64 bit) / Microsoft <sup>®</sup> Windows Server™ 2003 (32 bit/64 bit) / Microsoft <sup>®</sup> Windows Vista™ (32 bit/64 bit)	
Feed Detection Features	Ultrasonic Double Feed Detection Sensor	
	Intelligent Multifeed Function (Manual Bypass)	
Other Features	Embossed and Hard Card Scanning Capability, Long Document Scanning, Automatic Colour Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (in ADF only).	
Limited Warranty	One-year: Advance Exchange program also available; restrictions apply. For full details, visit <a href="http://www.ImagingService.com">www.ImagingService.com</a> or call (800) 626-4686.	
Service Options	Post-Warranty: Advance Exchange Plus; restrictions apply. Consumables: ScanAid™ kit. For full details, visit <a href="http://www.ImagingService.com">www.ImagingService.com</a> or call (800) 626-4686.	
Part Number	fi-6130	PA03540-B055
	fi-6230	PA03540-B555

<sup>1</sup> Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex. <sup>2</sup> Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher). <sup>3</sup> Actual scanning speeds are affected by data transmission and software processing times. <sup>4</sup> JPEG compressed figures. <sup>5</sup> Maximum capacity varies, depending upon paper weight. <sup>6</sup> Supports ISO7810 embossed cards. <sup>7</sup> Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm). <sup>8</sup> Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.) <sup>9</sup> The scanning of documents that exceed 35 inches in length will be limited to using TWAIN at 200 dpi or less. <sup>10</sup> Excluding the ADF paper chute and stacker. <sup>11</sup> PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).